



D30 Indoor Dome Camera

1/2.8" Progressive CMOS Sensor • Built-in IR Illuminators • P-iris Lens

Image Sensor	1/2.8" Progressive CMOS	LED Indicator	System power and status indicator
Maximum Resolution	2048x1536 (3MP)	Connectors	RJ-45 cable connector for Network/PoE connection
Lens Type	Varifocal	Power Input	IEEE 802.3af PoE
Focus	Autofocus	Power Consumption	11 W
Focal Length	f = 3 ~ 9 mm	Dimensions	Ø 145mm x 106mm / 5.7 inches x 4.2 inches
Aperture	F1.2 ~ F2.3	Weight	503g / 1.1 lb
Auto-iris	P-iris	Safety Certifications	IK08 vandal resistance FCC, ICES, IEC60950-1
Field of View	41° ~ 86° Horizontal 31° ~ 64° Vertical 51° ~ 113° Diagonal	Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Shutter Time	1/5 sec. to 1/16000 sec.	Humidity	90%
Day/Night	IR-cut filter for day & night function	Included Accessories	Setup guide, T10 security Torx screwdriver, screw pack, mounting template
IR Illuminators	30 meters in low light conditions	Ordering Information	D30-HW: Verkada Indoor Dome Camera

